

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ ☒ ☐

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Dry	7. Unit Agreement Name
2. Name of Operator Belco Petroleum Corporation	8. Farm or Lease Name Blanchard
3. Address of Operator P. O. Box 19234, Houston, Texas 77024	9. Well No. 1
4. Location of Well UNIT LETTER <u>B</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>11</u> TOWNSHIP <u>9-S</u> RANGE <u>34-E</u> NMPM.	10. Field and Pool, or Willamit Vada (Penn)
15. Elevation (Show whether DF, RT, GR, etc.) 4235' Gr.	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moved in Permian Basin Casing Pullers, Inc. of Odessa, Texas, and shot the 8-5/8" casing free at 1200'. Spotted 25 sacks of Class "H" Cement at 1200'. Spotted 25 sacks of Class "H" cement at 392' (base of surface casing). Pulled the remaining 8-5/8" casing out of the hole, then set a 10 sack plug of Class "H" cement at the surface. Erected a dry hole marker. The final plugging was finished on 4/14/71.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

James S. Black TITLE Petroleum Engineer - Agent DATE 4/28/71

APPR Nathaniel E. Mcgg TITLE OIL & GAS ENGINEER DATE 4/28/71
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

APR 20 1971

OIL CONSERVATION COMM.
HOBBS, N. M.