

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
1625 N. French Dr.
Hobbs, NM 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

Case Designation and Serial No.
NMNM0202771
6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Novy Oil & Gas, Inc.

3. Address and Telephone No.

125 N. MARKET ST., SUITE 1230, WICHITA, KS 67202 (316) 265-4651

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 1980' FWL SEC. 5 - T9S - R34E

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Sunoco #1

9. API Well No.

30-025-23689

10. Field and Pool, or Exploratory Area

VADA PENN

11. County or Parish, State

Lea County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☒ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*

1. MIRU - POOH w/rods & pump. Release tension anchor & POOH w/2 7/8" tbg.
2. Pick up packer & TIH on tbg. - set packer @ 9500'.
3. Acidize Bough "C" perfs - 9598-9620' w.2500 gal. 15% NE-FE acid. Flush acid w/60 bbl. 2% KCL wtr.
4. Release pkr. & POOH w/2 7/8" tbg. Lay dn. pkr.
5. Run 2 7/8" tbg. w/5 1/2" casing patch packer installed to TD. Set 5 1/2" anchor @ 9650' w/casing patch packer - 63' in length with top cups @ 8714' - bottom cups @ 8877' to seal off Abo perfs @ 8726' to 8768'. Set anchor w/13,000# tension.
6. Run pump & rods & put on pump.

Anticipate work to start March 1, 2001.

14. I hereby certify that the foregoing is true and correct

Signed

Frank E. Young

Title

PRESIDENT

Date

1/26/01

(This space for Federal or State office use)

Approved by

(ORIG. SGD.) LES BABYAK

Title

PETROLEUM ENGINEER

Date

FEB 14 2001

Conditions of approval, if any:

GW

SUNOCO FEDERAL #1
GAS VENT PACKER

