

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	2275	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____		T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____		T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	2886	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____		T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____		T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____		T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	4188	T. Simpson _____	T. Gallup _____	T. Ignacio Qizte _____
T. Glorieta _____		T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____		T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____		T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____		T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____		T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____		T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____		T. _____	T. Chinle _____	T. _____
T. Penn. _____		T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____		T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	2275	2275	Sand and Gravel				
2275	2886	611	Anhydrite and Salt				
2886	4188	1302	Sand, Shale & Dolomite				
4188	5040	852	Dolomite and Anhydrite				

RECEIVED

APR 7 1971

OIL CONSERVATION COMM.

HOBBS, N. M.