

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L-275	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole		7. Unit Agreement Name
2. Name of Operator Ard Drilling Company		8. Farm or Lease Name Hudson - State
3. Address of Operator P. O. Box 1030, Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER P, 660 FEET FROM THE East LINE AND 660 FEET FROM THE South LINE, SECTION 1 TOWNSHIP 10-S RANGE 32-E NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4185 GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☒  
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

We plan to start plugging operations on February 14, 1972.  
Anticipated casing recovery will be approximately 6000' of 5½" casing and 1200' of 8 5/8" casing.  
Plugs to be set as follows, with heavy mud between plugs.  
Cast Iron Bridge Plug to be set at 8795', which will be just above perforations at 8802' to 8818' and 8892' to 8902'.  
50 Sack cement plug at 6000' or in top of 5½" casing cut-off.  
35 Sack cement plug at 5300'  
50 Sack cement plug at 3332, bottom of 8 5/8" casing  
35 Sack cement plug at 1200' or in top of 8 5/8" casing cut-off.  
35 Sack cement plug at 390', bottom of 12 3/4" casing  
10 Sack cement at surface or top of 12 3/4" casing.  
Regulation Dry Hole Marker will be set.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Production Clerk DATE February 4, 1972  
APPROVED BY [Signature] TITLE SUPERVISOR DISTRICT I DATE FEB 7 1972  
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

FEB 7 1972

OIL CONSERVATION COMM.  
HOBBS, N. M.