

COUNTY	LEA	FIELD	Wildcat	STATE	NM	30-025-23773
OPR	ARD DRILLING CO.				MAP	
	1 Hudson-State					
	Sec 1, T-10-S, R-32-E				CO-ORD	
	660' FSL, 660' FEL of Sec					
	Spd 6-9-71		CLASS		EL	
	Cmp 2-14-72		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING						
12 3/4" at 390' w/375 sx						
8 5/8" at 3332' w/375 sx						
5 1/2" at 10,000' w/500 sx.						
LOGS EL GR RA IND HC A						
			TD 10,000'			
PLUGGED & ABANDONED						

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Ard PROP DEPTH 10,000' TYPE RT
DATE

F.R. 5-18-71; Opr's Elev. 4185' GL
PD 10,000' RT (Strawn)
Contractor - Ard

2-24-72 AMEND OPERATOR, Formerly reported as J. C. Barnes Oil Co.

6-1-71 AMEND OPERATOR & LEASE NAME, Formerly reported as Ard Drilg. Co. #1 Mescal - State.

6-12-71 TD 3332'; WOC

6-21-71 Drlg. 6375' 1m

6-28-71 Drlg. 8170' (Tight)

7-7-71 Drlg. 9230' (Tight)

7-13-71 TD 10,000'; Rng Logs (Tight)

7-19-71 TD 10,000'; Prep Swab
DST 8790-8830', open 1 hr, rec 180' VH&OCM +
1080' G&OC salt wtr + 3610' salt wtr, 1 hr ISIP
3027#, FP 940-2091#, 2 hr FSIP 3069#

7-19-71 Continued
DST 9180-9230', open 1 hr, rec 120' DM +
4809' salt wtr, 1 hr ISIP 2182#, FP 1368-2182#,
2 hr FSIP 2204#
DST 9780-9805', open 1 hr, rec 176' mud,
1 hr ISIP 1730#, FP 45-91#, 2 hr FSIP 1504#
Perf @ 8802', 8806', 8810', 8814', 8818' w/1 SPI
Acid (8802-18') 2000 gals
7-26-71 TD 10,000'; TO Pmp
Swbd 340 B form wtr w/rainbow show oil
8-2-71 TD 10,000'; TO Pmp
Ppd 485 BW in 24 hrs
8-9-71 TD 10,000'; TO Pmp
8-16-71 TD 10,000'; SD Pmp Repairs
8-23-71 TD 10,000'; TO Pmp

8-30-71 TD 10,000'; TO Pmp
Ppd 10 BO + 585 BW in 24 hrs (8802-18')
9-7-71 TD 10,000'; TO Pmp
9-13-71 TD 10,000'; TO Pmp
Ppd 19 BO + 935 BW in 24 hrs (8802-18')
10-5-71 TD 10,000'; TO Pmp
Ppd 15 BO + 825 BW in 24 hrs (8802-18')
10-11-71 TD 10,000'; TO Pmp
11-15-71 TD 10,000'; TO Pmp
11-22-71 TD 10,000'; TO Pmp
Perf 8805-14'
Acid (8802-18') 4000 gals
Ppd 19 BO + 840 BW in 24 hrs (8802-18')
11-29-71 TD 10,000'; TO Pmp
12-6-71 TD 10,000'; TO Pmp
Ppd 40 BO + 750 BW in 24 hrs (8802-18')

12-13-71 TD 10,000'; TO Pmp
12-20-71 TD 10,000'; SI
Perf 8892-8902' w/2 SPF
Acid (8892-8902') 2000 gals
Swbd 18 B salt wtr per hour (8892-8902')
1-3-72 TD 10,000'; TO Pmp
Ppd 812 BW in 24 hrs (8802-18')
1-10-72 TD 10,000'; TO Pmp
1-31-72 TD 10,000'; TO Pmp
2-7-72 TD 10,000'; Prep P&A
2-14-72 TD 10,000'; P&A (Holding for Tops)
2-21-72 TD 10,000'; PLUGGED & ABANDONED
LOG TOPS: San Andres 3419', Glorieta 4810',
Abo 7175', Bough "C" 8800', Cisco 9050',
Canyon 9160'

2-21-72 Continued
Well Drilled Tight
2-24-72 COMPLETION REPORTED