

NEW MEXICO OIL CONSERVATION COMMISSION

5a. Indicate Type of Lease

State ☐

Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-DRILL OR PLUG LATE TO A DIFFERENT RESERVOIR.  
(SEE APPLICATION FOR PERMIT TO DRILL OR RE-DRILL FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator  
The Maurice L. Brown Co.

3. Address of Operator  
Suite 200, Sutton Place Bldg., Wichita, Kansas 67202

4. Location of Well  
UNIT LETTER B 810' FEET FROM THE North LINE AND 1980' FEET FROM  
THE East LINE, SECTION 3 TOWNSHIP 9S RANGE 34-E NMPH.

7. Unit Agreement Name

6. Farm or Lease Name  
Atem

9. Well No.  
1

10. Field and Pool, or Wildcat  
Vada Penn

11. Elevation (Show whether DF, RT, GR, etc.)  
4259' GL

12. County  
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPS. ☐  
CASING TEST AND CEMENT JOG ☐  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒  
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Moved in and rigged up Permian Basin Casing Pullers, Inc.
2. Set cast iron bridge plug at 9553' and capped with 35' cement.
3. Picked up 2 3/3" tbg. and went in hole. Displaced hole with mud laden fluid.
4. Shot 5 1/2" csg. at 5419'. Layed down 132 Jts. (5419').
5. Spotted 35 sx. cement through tubing at 5469'.
6. Tagged top of cement at 5369'.
7. Spotted 35 sx. cement through tubing at 5300'.
8. Spotted 35 sx. cement through tubing at 3973'.
9. Tagged top of cement at 3868'.
10. Spotted 35 sx. cement through tubing at 2000'.
11. Shot 3 5/8" csg. at 1015'. Layed down 24 Jts.
12. Spotted 50 sx. cement through tubing at 1065'.
13. Tagged top of cement at 957'.
14. Spotted 70 sx. cement through tubing at 424'.
15. Tagged top of cement at 321'.
16. Spotted 10 sx. cement at surface.
17. Erected dry hole marker.
18. Rigged down casing pullers on 10-31-77.
19. Filled cellar and mud pit.
20. Leveled and cleaned location. Removed guy line anchors.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Wm. M. Groesbeck

TITLE District Engineer

DATE 2-14-78

APPROVED BY [Signature]

TITLE OIL & GAS INSPECTOR

DATE JUL 22 1980

CONDITIONS OF APPROVAL, IF ANY: