

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>

5. State Oil & Gas Lease No.
E-9236

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Belco Petroleum Corporation	8. Farm or Lease Name Midwest State
3. Address of Operator P. O. Box 19234, Houston, Texas 77024	9. Well No. #2
4. Location of Well UNIT LETTER F 1980 FEET FROM THE North LINE AND 2130 FEET FROM THE West LINE, SECTION 2 TOWNSHIP 9-S RANGE 34-E NMPM.	10. Field and Pool, or Wildcat Vada (Penn.)
15. Elevation (Show whether DF, RT, GR, etc.) 4252' GR.	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well at 6:00 o'clock P.M. on 5-26-71. Drilled a 17 1/2" hole to 375' KB. Ran and set 12-3/4" surface casing to 375' and cemented with 350 sacks of Class "C" cement with 2% Calcium Chloride. Plug down at 2:00 A.M. 5-27-71. The cement circulated. WOC for 18 hours and tested the casing to 600 psig for 30 minutes.

Drilled an 11" intermediate hole to 395 1/4' KB. Ran and set 8-5/8", 24#, 28# and 32# ST&C casing to 395 1/4' KB. Cemented the casing with 375 sacks of Class "C" cement with 2% Calcium Chloride. The plug was down at 5:00 A.M. on 6-1-71. WOC for 18 hours and tested the casing to 1500 psig for 30 minutes.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Warren D. Roach

TITLE Agent

DATE 6-9-71

APPROVED BY [Signature]

TITLE SUPERVISOR DISTRICT I

DATE JUN 11 1971

CONDITIONS OF APPROVAL, IF ANY: