

[illegible]

CONTR	OPRS ELEV	4230' DF	PD	4489'	TYPE	WO
-------	-----------	----------	----	-------	------	----

F.R.C. 4-28-73
(San Andres)
(Orig. Belco Pet. Corp., #1 U.S. Coastal,
Temp Aband 4-3-72, OTD 9100')
4-23-73 TD 9100'; PBD 4489'; COMPLETE
Ran 5 1/2" csg to 4489'
Perf 4239-52', 4259-61', 4964-70'
Acid (4239-70') 3000 gals
4-28-73 COMPLETION REPORTED

LEA
BELCO PET. CORP.

Wildcat NM Sec 31, T9S, R33E
1 U. S. - Coastal

Page #2

11-8-71 TD 9100'; PBD 9050'; RU Kobe Pmp
Perf (Bough "C") 9001-06', 9017-19' w/1 SPF
Acid (9001-19') 1000 gals
Swbd 1½ BO + 59 BFW + 131 BL&AW in 11 hrs
(9001-19')

11-15-71 Acid (9001-19') 2000 gals
11-22-71 TD 9100'; PBD 9050'; TO Pmp
TD 9100'; PBD 9050'; TO Pmp
Ppd 514 BW in 24 hrs
12-13-71 TD 9100'; PBD 9050'; TO Pmp
12-20-71 TD 9100'; PBD 9050'; TO Pmp
Ppd 8 BO + 317 BW in 24 hrs (9001-19')
1-3-72 TD 9100'; PBD 9050'; TO Pmp
Ppd 345 BW in 24 hrs (9001-19')

1-10-72 TD 9100'; PBD 9050'; TO Pmp
Ppd 299 BW in 24 hrs
1-17-72 TD 9100'; PBD 9050'; TO Pmp
Ppd 381 BW in 24 hrs (9001-19')
1-24-72 TD 9100'; PBD 9050'; TO Pmp
Ppd 273 BW in 24 hrs (9001-19')
2-7-72 TD 9100'; PBD 9050'; TO Pmp
2-14-72 TD 9100'; PBD 9050'; TO Pmp
2-21-72 TD 9100'; PBD 9050'; SI
Ppd 196 BW in 24 hrs (9001-19')
2-28-72 TD 9100'; PBD 9050'; SI
3-27-72 TD 9100'; PBD 9050'; SI
4-3-72 TD 9100'; PBD 9050'; TEMPORARILY ABANDONED
Will be Plugged & Abandoned @ Later Date
LOG TOP: Bough "C" 8996' (-4756')
4-8-72 COMPLETION REPORTED

COUNTY LEA FIELD Wildcat STATE NM 30-025-23889

MAP

OPR BELCO PET. CORP.

1 U. S. - Coastal

Sec 31, T-9-S, R-33-E

660' FSL, 660' FEL of Sec

Spd 9-30-71

Cmp 4-3-72

CLASS

EL 4230E

FORMATION	DATUM	FORMATION	DATUM

CSG & SX - TUBING

12 3/4" at 378' w/375 sx

8 5/8" at 3560' w/400 sx

5 1/2" at 9100' w/200 sx

LOGS EL GR RA IND HC A

TD 9100'; PBD 9050'

TEMPORARILY ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. McVay PROP DEPTH 9100' TYPE RT

DATE

F.R. 9-21-71

PD 9100' RT (Bough "C")

Contractor - McVay

10-4-71 Drlg. 720'

10-11-71 TD 4337'; Prep Drill

Cored 4249-94', rec 45', no descr

Cored 4294-4337', rec 43', no descr

10-18-71 Drlg. 7077'

10-25-71 Drlg. 8435'

11-1-71 TD 9100'; Rng 5 1/2" Casing

DST (Bough "C") 8775-8820', open 40 mins, rec 15'

DM, 1 hr ISIP failed, FP 66-79#, 1 hr FSIP 66#

DST 8998-9100', open 1 hr 10 mins, GTS 14 mins

@ TSTM, rec 200' HGCM + 2800' WC oil (50% oil),

+ 850' wtr, 1 hr ISIP 2738#, FP 680-1741#,

2 hr FSIP 2469#