

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate
(Other instructions on
reverse side)

Form Approved
Publications No. 42 R1424
5. LEASE DESIGNATION AND SERIAL NO.

NM-0103893-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Flag-Redfern Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 23, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FNL & 1980' FWL

Sec. 24, T-9S, R-37-E, Lea County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3970' Gr.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Brown "93"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Sawyer, San Andres

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 24, T-9-S, R-37-E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Well Progress

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent
to this work.)*

Drilled 7 7/8" hole from 425 feet to total depth of 5050 feet.

Ran Gamma Ray Neutron & Laterolog by Dresser Atlas.

Ran 29 jts. 4 1/2" 9.5 lb/ft., J-55 casing and set at 5049 feet.

Cemented casing with 250 sx Pozmix, 2% gel, 0.75% CFR-2,

8 lb. salt per sack. Plug down at 6:00 P.M. 12-16-71.

Tested casing with 1500 psig - OK.

WOC - 24 hours.

18. I hereby certify that the foregoing is true and correct

SIGNED

Quida Roach

TITLE Production Clerk

DATE 12/27/71

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
DEC 28 1971
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side