

COUNTY **LEA**
FIELD **Sawyer, W.**
STATE **NM** 30-025-24065

MAP
CO-ORD

OPR **OIL DEVELOPMENT CO. OF TEXAS**
14 SFPRR
Sec 27, T-9-S, R-37-E
1839' FSL, 2121' FEL of Sec
Spd 3-18-72
Cmp 4-1-72

	CLASS		EL	
	FORMATION	DATUM	FORMATION	DATUM

CSG & SX - TUBING
8 5/8" at 407' w/325 sx
4 1/2" at 5125' w/275 sx

LOGS EL GR RA IND HC A

TD 5125'; PBD 5115'
IP (San Andres) Perfs 4976-5000' P 68 BOED + 68 BW. Pot based on 24 hr test. GOR 652; Grav 22.3

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. **Sitton & Norton**
DATE

PROP DEPTH **5100'** TYPE **R**

3-20-72
3-27-72
4-3-72

4-10-72

4-15-72

F.R. 3-20-72; Opr's Elev. 3961' GL, 3971' KB
PD 5100' RT (San Andres)
Contractor - Sitton & Norton
Drlg. 2313'
TD 5125'; Prep run casing
TD 5125'; PBD 5115'; Swbg
Perf 4976-5000' w/1 SPF
Acid (4976-5000') 7000 gals
Swbd 9 BF (40% oil) in 4 hrs
TD 5125'; PBD 5115'; COMPLETE
LOG TOPS: Rustler 2297', Yates 2954', San And
4226', San Andres Porosity 4815', Slaughter
4976'
COMPLETION REPORTED

F.R. 3-20-72; Opr's Elev. 3961' GL, 3971' KB
PD 5100' RT (San Andres)
Contractor - Sitton & Norton
Drlg. 2313'
3-20-72 TD 5125'; Prep run casing
3-27-72 TD 5125'; PBD 5115'; Swtg
4-3-72 Perf 4976-5000' w/1 SPF
Acid (4976-5000') 7000 gals
Swbd 9 BF (40% oil) in 4 hrs
4-10-72 TD 5125'; PBD 5115'; COMPLETE
LOG TOPS: Rustler 2297', Yates 2954', San Andres
4226', San Andres Porosity 4815', Slaughter
4976'
4-15-72 COMPLETION REPORTED