

COPIES RECEIVED	
DISTRIBUTION	
DATE	
BY	
S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐		5a. Indicate Type of Lease State ☐ Fee ☒
Name of Operator Coastal States Gas Producing Company		5. State Oil & Gas Lease No.
Address of Operator P. O. Box 235, Midland, Texas 79701		7. Unit Agreement Name
Location of Well UNIT LETTER B 660 North 1980 THE East LINE, SECTION 8 TOWNSHIP 9-S RANGE 34-E		8. Former Lease Name W. T. Hutherson
15. Elevation (Show whether DE, RT, GR, etc.) 4288.6 GR.		9. Well No. 1
12. County Lea		10. Field and Pool, or Wildcat Vada Penn

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK	☐	PLUG AND ABANDON	☒
TEMPORARILY ABANDON	☐	CHANGE PLANS	☐
PULL OR ALTER CASING	☐	OTHER	☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK	☐	ALTERING CASING	☐
COMMENCE DRILLING OPERATIONS	☐	PLUG AND ABANDONMENT	☐
CASING TEST AND CEMENT JOB	☐		

1. Describe proposed or completed operations if timely state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Notify New Mexico Oil Conservation Commission, District Office in Hobbs 24 hours prior to beginning plugging operations.
2. Set CIBP at 9650' (Perf. 9674-92) and spot 25' of cement on top of plug.
3. Displace well fluids with mud containing 25 sx salt gal per 100 bbls. brine. This type mud will be left between all plugs.
4. Determine free point, cut off and pull recoverable 5½" casing.
5. Spot 100' cement plug in and out of casing stub.
6. Determine free point in 8 5/8", cut off and pull recoverable casing.
7. Spot 100' cement plug in and out of casing stub.
8. Spot 100' cement plug in and out of bottom of 13 3/8" surface casing.
9. Cap at surface with 10' cement plug.

14. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. R. Woods Senior Petroleum Engineer DATE 7-15-75

APPROVED BY John W. Remyan TITLE DATE JUL 17 1975

CONDITIONS OF APPROVAL, IF ANY:

* Spot 100' plugs at top of Abo, Glorieta and top of Salt if not behind pipe.