

COUNTY	LEA	FIELD	Crossroads	STATENM	30-025-24144
OPR	OIL DEVELOPMENT CO. OF TEXAS			MAP	
3 SFPRR "27"					
Sec 27, T-9-S, R-36-E				CO-ORD	
990' FNL, 2310' FWL of Sec					
Spd 6-7-72					
Cmp 8-3-72					
		CLASS		EL	
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
13 3/8" at 315' w/300 sx					
8 5/8" at 5000' w/400 sx					
5 1/2" at 11,987' w/350 sx					
LOGS EL GR RA IND MC A					
		TD 12,018'			

IP (Siluro-Devonian) Perfs & OH 11,971-12,018' P 190 BOPD + 14 BW.
Pot based on 24 hr test. GOR TSTM; Grav 44

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Consulting Services, Inc.

CONT.	Sharp	PROP DEPTH	12.100'	TYPE	RT
DATE					

F.R. 5-29-72; Opr's Elev. 4033' GL
PD 12,100' RT (Devonian)
Contractor- Sharp
6-12-72 Drlg. 4044'
6-20-72 TD 5000'; Prep cmt 8 5/8" csg
Cored 4790-4848', rec 58' being 13' dense dolo,
streaks anhy, NS, 45' anhy dolo, scat poro, bldg
oil
Cored 4848-4906', rec 58' anhy dolo, scat poro,
bldg oil
6-26-72 Drlg. 7440'
7-10-72 Drlg. 10,662'
7-17-72 Drlg. 11,710'
7-25-72 TD 11,992'; PBD 11,775'; MORT
7-31-72 TD 11,992'; PBD 11,775'; Prep Drill cmt
Perf 11,930-940' (csg sqze)
Sqzd 11,930-940' w/50 sx
8-7-72 TD 11,992'; PBD 11,990'; SI

8-7-72 Continued
Perf 11,971-985' w/1 SPF
Acid (11,971-985') 500 gals
Swbd 10-12 BOPH (11,971-985')
Acid (11,971-985') 3000 gals
Swbd 145 BO in 8 hrs
8-15-72 TD 11,992'; PBD 11,990'; Tstg
Swbd 175 BO in 8 hrs (11,971-985')
8-21-72 TD 11,992'; PBD 11,990'; RU Pmp
8-28-72 TD 11,992'; PBD 11,990'; SD Pmp Repairs
9-5-72 TD 12,011'; Swbg
Deepened from 11,992' to 12,011'
9-11-72 TD 12,011'; Tstg
9-18-72 TD 12,011'; Prep Acid OH
9-26-72 TD 12,011'; Swbg

9-26-72 Continued
Acid (11,987-12,011') 3000 gals (20%)
Swbd 140 BF (25% wtr) (75% oil) in 9 hrs
(11,971-12,011')
10-2-72 TD 12,011'; Drlg cmt
Perf @ 11,930' & 11,940'
Sqzd 11,930-940' w/50 sx
10-9-72 TD 12,018'; Prep RU Pmp
Drilled to 12,018'
Acid (11,987-12,018') 5000 gals
Swbd 120 BF (20% wtr) in 8 hrs (11,971-12,018')
10-16-72 TD 12,018'; SD Pmp Repairs
Ppd 50 BO + 3 BW in 7 hrs (11,971-12,018')
10-23-72 TD 12,018'; WO Potential
Ppd 190 BO + 14 BW in 24 hrs
10-30-72 TD 12,018'; COMPLETE

LEA

Crossroads

NM Sec 27, T9S, R36E

OIL DEVELOPMENT CO. OF TEXAS 3 SFPRR "27" Page #3

10-50-72

Continued

LOG TOPS: Glorieta 5518', Clearfork 6168',
Tubb 6903', Abo 7682', Wolfcamp 8897',
Pennsylvanian 9228', Bough "C" 9579', Canyon 9957',
Strawn 10,450', Atoka 10,668', Morrow 10,894',
Mississippian 11,396', Woodford 11,844', Devonian
11,910'

11-4-72

COMPLETION REPORTED