

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy 2100'	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt 2167'	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2694'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2890'	T. Devonian	T. Menefee	T. Madison
T. Queen 3500'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres 3910'	T. Simpson	T. Gallup	T. Ignacio Qtzte
T. Glorieta 5344'	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinbry	T. Gr. Wash	T. Morrison	T.
T. Tubb 6836'	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand	T. Entrada	T.
T. Abo	T. Bone Springs	T. Wingate	T.
T. Wolfcamp 8924'	T.	T. Chinle	T.
T. Penn.	T.	T. Permian	T.
T. Cisco (Bough C) 9660'	T.	T. Penn. "A"	T.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0'	2100'		Red Beds, shale & sand				DST #1 9629-9715' 1:15
2100'	2167'		Anhydrite				GTS 18", rec. 60' mud,
2167'	2694'		Salt & Anhydrite				1258' oil, 1193' salt water
2694'	2890'		Sand & Anhydrite				IF 778#, FF 1074# on 15"
2890'	3500'		Anhydrite & Dolomite				preflow. ISIP 1821#, 120"
3500'	3910'		Sand, Anhydrite & Dolomite				FSIP 1821#, 64" IF 800#,
3910'	5344'		Dolomite, Lime & Anhydrite				FF 1142#. No cores.
5344'	6836'		Sand, Dolomite & Anhydrite				
6836'	7712'		Sand & Dolomite				
7712'	8924'		Red & Green shale, Dolomite & Anhydrite				
8924'	TD		Lime & shale				

RECEIVED

SEP 11 1972

OIL CONSERVATION COMM.
HOBBS, N. M.