

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
-	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Read & Stevens, Inc.		8. Farm or Lease Name Sheridan "Com"
3. Address of Operator P.O. Box 2126, Roswell, New Mexico 88201		9. Well No. 1
4. Location of Well UNIT LETTER <u>D</u> <u>554</u> FEET FROM THE <u>North</u> LINE AND <u>554</u> FEET FROM THE <u>West</u> LINE, SECTION <u>19</u> TOWNSHIP <u>9S</u> RANGE <u>34E</u> NMPM.		10. Field and Pool, or Wildcat Vada Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4308.5' GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 297 jts. of 5½" csg. - 15½# to 17# - N-80, K-55 & J-55 to 9735.26'; set at 9715' RKB. Cmt. w/400 sx. Class C Poz w/12% gel, 8# salt/sx. plus 100 sx. Class C. Pmp 500 gals mud flush ahead of cement. Centralizers on 1st, 2nd and 3rd jts. Scratchers on 2nd, 3rd and 4th jts. Plug down at 3:45 A.M. 8/9/72. Tested csg. to 2000# for 30 minutes. Held OK. Ran csg. as follows:

26 jts. 17# J-55 Butt (used)	1042.72
116 jts. 15.5# J-55 LT&C (used)	3699.32
31 jts. 15.5# J-55 ST&C (used)	955.10
49 jts. 17# K-55 ST&C (new)	1595.82
75 jts. 17# N-80 LT&C (new)	2401.30
1 Guide Shoe	1.00
	9735.26

Temp. Survey cement top at 6520'

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Agent DATE 8/28/72

APPROVED BY Joe D. Ramsey TITLE Dist. I, Supv. DATE SEP 5 1972

CONDITIONS OF APPROVAL, IF ANY: