NO. OF COPIES RECEIVED	1		Form C-103
DISTRIBUTION			Supersedes Old
SANTA FE	NEW MEXICO OIL CONS	ERVATION COMMISSION	C-102 and C-103
FILE		ERTATION COMMISSION	Effective 1-1-65
U.S.G.S.			5a. Indicate Type of Lease
			State Fee
OPERATOR			5. State Oll & Gas Lease No.
	1		
SUNDE	V NOTICES AND REPORTS ON	WELLS	
(DO NOT USE THIS FORM FOR PRO USE "APPLICAT	AND TICES AND REPORTS ON DESALS TO DRILL OR TO DEEPEN OR PLUG B	WELLS ACK TO A DIFFERENT RESERVOIR. H PROPOSALS.)	
1.			7. Unit Agreement Name
OIL GAS WELL	OTHER-		
2. Name of Operator			8. Farm or Lease Name
We above Datas Barrow Commence			
3. Address of Operator	y. Well No.		
P. O. Box 36666, He 4. Location of Well	10. Field and Pool, or Wildcat		
UNIT LETTER	1980 FEET FROM THE East	LINE AND FEET FF	hatereisebay / M perivir
THE North LINE, SECTI	on6 Township105	RANGE 338 NM	™. (()))))))))))))))))))))))))))))))))))
	15, Elevation (Show whether	DF, RT, GR, etc.)	12. County
^{16.} Check	Appropriate Box To Indicate N	ature of Notice Report or	Other Data
	NTENTION TO:	. -	INT REPORT OF:
		000002402	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB	FLOG AND ABANDONMENT
		A	. [7]
OTHER		Correct Elevat	ion & Name Contractor
	perations (Clearly state all pertinent deto	uils, and give pertinent dates, includ	ling estimated date of starting any proposed
work) SEE RULE 1103.			
Correct elevation fro	om estimated 4200' GL sho	wn on Form C-101 to 4	198.1 GL
Hondo Drilling Compar	ny - Drilling Contractor.	,	
•	2 #, J-55 casing set at 36	•	
	Class A cement with 2%	Calcium Chloride (100	t excess).
Plug down 2:00 AM 10-			
Circulated 25 sxs cer	ment to surface (5bbls).		
Option 2:			
250 sxs Halliburton (Class A cement with 2% ca	lcium chloride (340	cu. ft.)
Mixing temperature (a	umbient) 85°F.		
Minimum formation ter	perature 60°F.		
Estimated cement stre	angth at time of test - 7	/63 psi.	
	place prior to test - 1	-	
	nours. Nippled up Head a		
	and rams to 6000psi for		#/gal.
mud, no pressure drop			
· •	at 5:00 PM 10-6-72 (15	hours).	

Drilled plug and shoe at 5:00 PM 10-6-72 (15 hours). 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

.

SIGNED _ R. B. Theff		DATE -10-19-72
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	Orig. Signed by Joe D. Ramoy TITLE Dist. I, Supar.	OCT 24 1972

RECEIVED

. .

· • •

GOT 23 1972

OLL CONSERVATION COMM. HOBBS, N. M.

