

MAYO MARRS CASING PULLING INC.
FIELD REPORT

NEW MEXICO OCD
ATTN: CHRIS WILLIAMS
Lease: SANTA FE PACIFIC
WELL # 4
Project: P & A

30-025-24289
OPERATOR: METEOR DEVELOPMENTS, INC.
22-95-360 330/5 & 2310/10
DATE 8-24-98

8-03-98
MIRU - RIH WITH TUBING - TAG PLUG @ 7050' - CLOSE IN WELL
(10 HRS RIG)

8-04-98
POOH W/TBG - RIH WITH 4 1/2" BIT - RIG UP REVERSE UNIT - DRILLING
FOR 4 HRS - DRILL 18 INCHES - POOH 10 STANDS - CLOSE IN WELL
(12) (USE 240 BBLs WATER)

8-05-98
LOWER TUBING - START DRILLING - DRILL 1' - LAY DOWN SWIVEL - SPOT
25 SXS @ 7050' - POOH - WOC - TAG PLUG @ 7040' - RESET PLUG @ 7040'
WITH 25 SXS - POOH - CLOSE IN WELL
(13) (USE 100 BBLs WATER)

8-06-98
RIH WITH TBG AND TAG @ 6,922' - POOH WITH TUBING - PERFORATE @ 5564'
RIH WITH 7" PACKER TO 2000' - NO INJ. RATE @ 800# - HOLD FOR 15
MINUTES - POOH - RIH OPEN ENDED TO 5614' - SPOT 25 SXS - POOH - CION
(12)

8-07-98
BREAK DOWN BRADEN HEAD - WELD ON - CUT CASING @ 4200' - NOT FREE -
WORK CASING - CION
(9)

8-10-98
RE CUT CASING @ 4200' - START LAYING DOWN CASING -
(13)

8-11-98
LAY DOWN REST OF CASING - NUBOP - RIH WITH TUBING TO 4250' - MIX MUD
SPOT 45 SXS - POOH - WOC - NO TAG - RES POT 35 SXS @ 4250' - POOH -
(12)

8-12-98
TAG PLUG @ 4142' - MIX 285 BBLs MUD (140 SXS GEL) - POOH & SPOT 50
SXS @ 2325' - POOH - PERFORATE 9 5/8" CASING @ 359' - RIH WITH
9 5/8" PACKER - SQUEEZE 75 SXS - WOC - TAG CEMENT @ 248' -
(12)

8-13-98
SPOT 15 SXS @ 30' TO SURFACE - CUT OFF WELLHEAD - INSTALL DRY HOLE
MARKER - RIG DOWN
(6)