1.0. OF COPIES RECEIVED	D						Form C-	103			
DISTRIBUTION								Supersedes Old			
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION						C-102 and C-103 Effective 1-1-65				
FILE								- 11 05			
U.S.G.S.							5a. Indicate	Type of Lease			
LAND OFFICE							State	F	ee X		
OPERATOR							5. State Oil	& Gas Lease No.			
							-				
	STINDE	V NOTICES	AND DEDO	DTS ON	WELLS		mm	mmm	mm.		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)											
1.							7. Unit Agre	eement Name	777777		
OIL X GAS WELL OTHER-											
2. Name of Operator								_ease Name			
Apache Exploration Corporation							- 1	Caldwell Comm.			
3. Address of Operator								9. Well No.			
P. O. Box 2299, Tulsa, Oklahoma 74101							1				
4. Location of Well								nd Pool, or Wilder	at		
								· ·			
UNIT LETTER H , 1980 FEET FROM THE NORTH LINE AND 660 FEET FROM								TRIIBLEG	m		
Post		10		Od		0.05					
THE East LINE, SECTION 12 TOWNSHIP 98 RANGE 33E NMPM											
mmmm	mm		Ilougation (Sho	an anhathar	DF, RT, GR, etc	_ 1	12. County	<i>m) </i>	HHH		
		///////////		4316.9	Dr, Kr, GK, etc	U•)					
							Lea		777777		
	Check A	Appropriate 1	Box To Ind	dicate N	ature of Not	ice, Report or C	Other Data				
NC	TICE OF IN	TENTION TO	0:	1		SUBSEQUE	NT REPORT	OF:			
				:	F?						
PERFORM REMEDIAL WORK	· 🛄		PLUG AND ABA	NDON	REMEDIAL WOR	к 🔲		LTERING CASING			
TEMPORARILY ABANDON					COMMENCE DRI	LLING OPNS.	F	LUG AND ABANDON	MENT		
PULL OF ALTER CASING			CHANGE PLANS	s 🔲	CASING TEST A	ND CEMENT JOB					
·					OTHER			-			
OTHER											
		(61 - 1			., ,						
17. Describe Proposed o work) SEE RULE 11		erations (Cleari	y state all pe	rtinent aeti	uis, ana give pe	rtinent dates, includi	ng estimated da	e of starting any	proposed		
11/30/72	Smidded	15" surfac	ce bole	at 1:30	h has MA (rilled to 38'	S KR Ro	n 3881			
11/30/72 Spudded 15" surface hole at 1:30 AM and drilled to 385 of 11 3/4" OD 42# H-40 ST&C new casing & set at 385 KB											
	cemented w/ 350 sks. Class "C" w/ 2% CaCl. Plug down a										
11-30 w/ good cement returns. Cut off csg., nippled up											
preventer equipment & tested to 800 psi for 30 mins.											
	prevence	r cdarbuc	ne a ceb	LCG LO	OOO PEL L	or 30 mins.	AII HEIG	OK			
12/01/72	Drillod	OFIIG to / 1	1# bolo	to 30/1	i in lima	Dan 02 44	E O E /	oli On			
12/01/12	72 Drilled OFUS w/ 11" hole to 3945' in lime. Ran 93 jts. of 8 5/8" OD 24 & 32# K-55, ST&C new and used casing set at 3945'. Cemented w/										
						at 3:00 AM,		w/			
	3/3 5%5.	Class C	W/ 2/6	Cacr.	riug down	at 3:00 AM,	12/0//2				
12/06/72	Sot alin	a and min	n1 od	מאס	damant	Tontod to 1 (000 -at fa	20			
12/00//2						Tested to 1,0		r 30			
	mrus. c	nerd OK.	rrep. t	o drii:	. anead w/	7 7/8" hole	•				
					 						
18. I hereby certify that	the information	above is true ar	nd complete to	o the best o	t my knowledge	and belief.					
<i>-</i>	1 1	V -	, /								
SIGNED Day	- he	Jones	<u></u> -	TTLE Reg	onal Prod	uction Manage	ET DATE_	Dec. 8, 19	72		
		3-33									
•		Orig. Sign	ned by				_	EO 104	072		
APPROVED BY		Joe D. 1		TTLE	<u> </u>		DATE	EC 181	J16		
CONDITIONS OF APPRO	OVAL, IF ANY	Diet T	•								
and the second s	-		-								