

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE  
(Other instructions  
verse side)

TE\*  
re

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-2390-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Bilbrey 90

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

undesignated

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 14 T-9-S R-37-E

12. COUNTY OR PARISH 13. STATE

Lea

N.M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Flag-Redfern Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 23, Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1980' FSL & 1980' FEL, Section 14, T-9-S, R-37-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3990' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Casing - surface 8-5/8" set at 421'. Production - 4 1/2" set at 5009'

Perforations - 4903,05,06,09,13,17,25,27,65,66,67,68,69,71 - San Andres Formation

Reason for Abandonment - Swabbing at rate of 6 barrels formation water per hour,  
trace of oil

ABANDONMENT PROCEDURE

Ran cast iron bridge plug on wireline and set at 4885'. Dump 10' cement plug on top of bridge plug with dump bailer. Shoot 4 1/2" casing at 4000'. Circulate hole with gel. Spot 35 sack cement plug from 4000' back to 3900'. Pull casing. Spot 35 sack cement plug from 471' back to 371'. Spot 10 sack plug at surface and weld marker.

AMENDMENT:

1. Cement plug on top of bridge plug must be minimum of 35 feet in length.
2. Spot additional 100 foot cement plug at 2000-2100 feet.

18. I hereby certify that the foregoing is true and correct

SIGNED

*[Signature]*

TITLE Production Manager

DATE 6-6-73

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

**APPROVED**  
AS AMENDED  
JUN 7 1973

ARTHUR R. BROWN  
DISTRICT ENGINEER

\*See Instructions on Reverse Side