

IP (Bough "C") Perfs 9532-58' P 430 BOPB + 560 RW. Pot based
on 24 hr test. GOR 350; Grav 47

CONTR	MCF	OPRS ELEV	4347'	GL	PD	9600'	TYPE	RT
-------	-----	-----------	-------	----	----	-------	------	----

F.R. 8-20-73
(Formerly Aban. Loc. 4-30-73 as Hanson Oil Corp., #2 Midwest State)
8-13-73 Drilg 4643'
8-20-73 Drilg 7778'
8-27-73 Drilg 8580'
9-4-73 TD 9575'; Eng Logs
9-11-73 TD 9610'; WOO
DST 9585-73', open 2 hrs 30 mins, GTS in 25 mins, no Bat, (Sampler rec 2.4 CFG + 600 cc's oil + 1200 cc's wtr), 2 hr ISIP 1632#, FP 487-1210#, 2 hr PSIP 1621#, HP 4887-4887#
9-18-73 TD 9610'; WOOB
10-4-73 TD 9610'; WOOB

LEA

Vada

NM

STALLWORTH OIL & GAS CO. 1 Midwest State
Sec 2, T9S, R33E

Page #2

 TD 9610'; WOCU
11-1-73 TD 9610'; Prep Perf
11-7-73 TD 9610'; SD
Perf 9532-58' w/2 SPF
Acid (9532-58') 2000 gals (15%)
Swbd 204 BF (39 BO + 165 BW) in 24 hrs
(9532-58')
11-14-73 TD 9610'; SD
12-12-73 TD 9610'; WO Tank Battery
12-20-73 TD 9610'; WO Corrected Pot
Pump Malfunctions
12-31-73 TD 9610'; COMPLETE
LOG TOP: Bough "C" 9525'
1-5-74 COMPLETION REPORTED

FR 3-19-73
(Bough "C")
5-7-73 ABANDONED LOCATION
5-12-73 COMPLETION REPORTED