

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLI  
(Other instructions  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER Dry Hole		5. LEASE DESIGNATION AND SERIAL NO. NM 0337995
2. NAME OF OPERATOR Julian Ard		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 1030 - Midland, Texas 79701		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' from West line and 660' from South line of Section 15, T-9-S, R-37-E		8. FARM OR LEASE NAME Billbrey-Federal
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3975 Ground Level		10. FIELD AND POOL, OR WILDCAT Sawyer, West
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 15, T-9-S, R-37-E
		12. COUNTY OR PARISH Lea
		13. STATE N.M.

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

We plan to commence plugging operations May 18, 1973.

Casing recovery is estimated to be approximately 4000 feet of 4-1/2" casing.

Plugs will be set as follows, with 10# Salt Base Mud between plugs.

Plug #1 - Cast Iron Bridge Plug set at 4900' with 35 sack cement plug on top

Plug #2 - 35 sack cement plug at top of 4-1/2" casing

Cut-off, approximately 4000'

Plug #3 - 35 sack cement plug at 2150'

Plug #4 - 35 sack cement plug at 410', bottom of 8-5/8" surface casing.

Plug #5 - 10 sack cement plug at surface or top of 8-5/8" casing.

Regulation dry hole marker will be set.

Verbal approval for above plugging operations received 5-17-73

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Agent

DATE May 17, 1973

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

MAY 21 1973

ARTHUR R. BROWN  
DISTRICT ENGINEER

\*See Instructions on Reverse Side