

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions
verse side)Form approved.
Bureau No. 42-R-424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM 0337995
2. NAME OF OPERATOR Julian Ard		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 1030 - Midland, Texas 79701		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' from West line and 660' from South line of Section 15, T-9-S, R-37-E		8. FARM OR LEASE NAME Bilbrey-Federal
14. PERMIT NO.		9. WELL NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3975 Ground Level		10. FIELD AND POOL, OR WILDCAT Sawyer, West
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 15, T-9-S, R-37-E
		12. COUNTY OR PARISH Lea
		13. STATE N.M.

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Cement job on surface casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well spudded at 11:30 AM, 4-28-73. Drilled 12-1/4" hole to 462 feet.
Ran 424 feet of 8-5/8" O.D. 8 rd. thread, 24#, K-55, Range 2,
Seamless casing, set at 410 feet, cemented with 250 sacks Class "C"
Cement, 2% Calcium Chloride. Plug down at 9:00 PM, 4-28-73.
Cement circulated. Pressured up on 8-5/8" casing with 750# for thirty
minutes, held okay.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE

5-4-73

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAY 7 1973

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side