

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

(Other Instructions
verse side)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

New Mexico 0421214

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Harris Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

35-9S-32E

12. COUNTY OR PARISH 13. STATE

Lea

New Mex.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Texas Crude, Inc.

3. ADDRESS OF OPERATOR

915 Houston Citizens Bank Bldg., 1010 Jefferson St., Houston, Tx 77002

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2310/N - 1980/E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4282 CE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Sept 11, 1973 Moved in workover unit, displaced water with oil. Spotted 500 Gal. Dowell perforating acid no 1. Perforated 4393-4397 with 3 holes. Ran tubing with packer. Broke formation at 1600#. Inj P 2400# to 3000#, inj 4 PBM. Swab tested 2 BPH 2% oil & 98% water.

Sept. 13, 1973 Pulled tubing set bridge plug @ 4250. Perforated 4176-4198 with 10 holes. Acidized with 250 gal. Dowell perforating acid no 1. BPD 1500# Inj P 1500# Inj R 4 BPH. Swab tested 1.5 BPH, 1.5% oil & 98.5% water.

Sept. 15, 1973 Displaced hole with 9.5 mud, pull tubing, Welox set bridge plug at 4170 with 3 sx cement on top of plug, top of cement 4133.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Dist. Supt.

DATE

9-17-73

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

SEP 17 1973

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO