

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator John L. Cox	8. Farm or Lease Name Roil
3. Address of Operator 408 West Wall, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>H</u> <u>2121</u> FEET FROM THE <u>North</u> LINE AND <u>519</u> FEET FROM THE <u>East</u> LINE, SECTION <u>21</u> TOWNSHIP <u>9S</u> RANGE <u>37E</u> NMPM.	10. Field and Pool, or Wildcat West Sawyer (San Andres)
15. Elevation (Show whether DF, RT, GR, etc.) 3975.9 GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12 $\frac{1}{4}$ " hole September 28, 1973, 3:00 p.m.

Drilled 12 $\frac{1}{4}$ " hole to 424'. Set 8 5/8", 20#, H-40 casing @ 424' with 325 sx. Class H cement with 2% Calcium Chloride. Cement circulated.

WOC 24 hrs.

Tested casing with 1,000# for 30 minutes - test OK.

Started drilling ahead in 7 7/8" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Martha Wittenbach TITLE Production Clerk DATE 10-2-73

APPROVED BY John D. Lunny TITLE Production Clerk DATE 10-2-73

CONDITIONS OF APPROVAL, IF ANY: