

|                               | O. D. | I. D.  | LENGTH     | DEPTH |
|-------------------------------|-------|--------|------------|-------|
| Drill Pipe or Tubing          | 6.00" | 2.62"  | 1.00'      |       |
| Reversing Sub                 |       |        |            |       |
| Water Cushion Valve           |       |        |            |       |
| Drill Pipe                    | 4.50" | 3.826" | 8419'      |       |
| Drill Collars                 | 6.25" | 2.25"  | 720'       |       |
| Handling Sub & Choke Assembly |       |        |            |       |
| Dual CIP Valve                |       |        |            |       |
| Dual CIP Sampler              |       |        |            |       |
| Hydro-Spring Tester           | 5.00" | .75"   | 4.00'      | 9139' |
| Multiple CIP Sampler          | 5.00" | .75"   | 4.00'      |       |
| Extension Joint               | 5.00" | .87"   | 10.00' (2) |       |
| AP Running Case               |       |        |            |       |
| Hydraulic Jar                 | 5.00" | 1.75"  | 5.00'      |       |
| VR Safety Joint               | 5.00" | 1.00"  | 3.00'      |       |
| Pressure Equalizing Crossover |       |        |            |       |
| Packer Assembly               | 6.75" | 1.53"  | 5.00'      | 9167' |
| Distributor                   | 5.00" | 1.68"  | 2.00'      |       |
| Packer Assembly               | 6.75" | 1.53"  | 5.00'      | 9174' |
| Flush Joint Anchor            |       |        |            |       |
| Pressure Equalizing Tube      |       |        |            |       |
| Blanked-Off B.T. Running Case |       |        |            |       |
| Drill Collars                 |       |        |            |       |
| Anchor Pipe Safety Joint      |       |        |            |       |
| Packer Assembly               |       |        |            |       |
| Distributor                   |       |        |            |       |
| Packer Assembly               |       |        |            |       |
| Anchor Pipe Safety Joint      | 5.75" | 1.50"  | 4.00'      |       |
| Side Wall Anchor              |       |        |            |       |
| Drill Collars                 | 6.25" | 2.25"  | 56.00'     |       |
| Flush Joint Anchor            | 5.75" | 3.50"  | 16.00'     |       |
|                               | 5.75" | 3.50"  | 5.00'      | 9250' |
| Blanked-Off B.T. Running Case | 5.75" | 3.50"  | 4.00'      | 9255' |
| Total Depth                   |       |        |            |       |