

NO. COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L-494	

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Stallworth Oil & Gas		8. Farm or Lease Name Midwest-State
3. Address of Operator 407 West Missouri Avenue, Midland, Texas 79701		9. Well No. 2
4. Location of Well UNIT LETTER <u>F</u> <u>1980</u> FEET FROM THE <u>West</u> LINE AND <u>1980</u> FEET FROM THE <u>North</u> LINE, SECTION <u>2</u> TOWNSHIP <u>9-S</u> RANGE <u>33-E</u> NMPM.		10. Field and Pool, or Wildcat <u>Stallworth</u>
15. Elevation (Show whether DF, RT, GR, etc.) 4341' GL		12. County Lea

### 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plug and abandon; formation tops: Salt 2035', Yates 2592', Queen 3045', San Andres 3795', Glorieta 5245', Tubb 6750', Abo 7620', Brothers 9215', Bough "C" 9537'. Original total depth 9610', PBTD 9587'; perforations 9540-9561', 5-1/2" casing. Set cast iron bridge plug at 9500'; 35' of cement on top of C.I.B.P. Pull approximately 6000'+ 5-1/2" casing; 100' of cement plug at stub 5-1/2" casing; 100' plug at Glorieta if uncovered, 100' plug in and out 8-5/8" shoe at 3900'. Pull approximately 1200'+ casing, 100' plug at stub of 8-5/8", 100' plug at Salt if uncovered, 100' plug in and out surface casing set at 390', 10 sack plug at surface and proper dry hole marker. Hole will be loaded with 9# mud laden fluid. Work to start May 15, 1975.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Rubert R. Morris TITLE Field Superintendent DATE 4-22-75

APPROVED BY [Signature] TITLE [Signature] DATE [Signature]  
CONDITIONS OF APPROVAL, IF ANY: [Signature]