

|                               | O. D.  | I. D.  | LENGTH   | DEPTH |
|-------------------------------|--------|--------|----------|-------|
| Drill Pipe or Tubing          | 6 1/4" | 3.50"  | 1'       |       |
| Reversing Sub                 |        |        |          |       |
| Water Cushion Valve           |        |        |          |       |
| Drill Pipe                    | 4 1/2" | 3.826" | 8029'    |       |
| Drill Collars                 | 6 1/4" | 2.25"  | 861'     |       |
| Handling Sub & Choke Assembly |        |        |          |       |
| Dual CIP Valve                |        |        |          |       |
| Dual CIP Sampler              |        |        |          |       |
| Hydro-Spring Tester           | 5"     | .75"   | 4'       | 8897' |
| Multiple CIP Sampler          | 5"     | .75"   | 4'       |       |
| Extension Joint               | 5"     | .875"  | 10' (2)' |       |
| AP Running Case               | 5"     | 3.87"  | 4'       | 8915' |
| Hydraulic Jar                 | 5"     | 1.75"  | 5'       |       |
| VR Safety Joint               | 5"     | 1.00"  | 3'       |       |
| Pressure Equalizing Crossover |        |        |          |       |
| Packer Assembly               | 7 3/4" | 1.53"  | 6'       | 8927' |
| Distributor                   | 5"     | 1.68"  | 2'       |       |
| Packer Assembly               | 7 3/4" | 1.53"  | 6'       | 8935' |
| Flush Joint Anchor            |        |        |          |       |
| Pressure Equalizing Tube      |        |        |          |       |
| Blanked-Off B.T. Running Case |        |        |          |       |
| Drill Collars                 |        |        |          |       |
| Anchor Pipe Safety Joint      | 5 3/4" | 1.50"  | 4'       |       |
| Packer Assembly               |        |        |          |       |
| Distributor                   |        |        |          |       |
| Packer Assembly               |        |        |          |       |
| Anchor Pipe Safety Joint      |        |        |          |       |
| Side Wall Anchor              |        |        |          |       |
| Drill Collars                 |        |        |          |       |
| Flush Joint Anchor            | 5 3/4" | 3.50"  | 8'       |       |
| Blanked-Off B.T. Running Case | 5 3/4" | 2.50"  | 6'       | 8949' |
| Total Depth                   |        |        |          |       |