

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

## SUNDY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR RE-ENTER OR RE-LEASE TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - FORM C-101 FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Shell Oil Company	8. Form or Lease Name State
3. Address of Operator P. O. Box 1509, Midland, TX 79702	9. Well No. 2
4. Location of Well UNIT LETTER <u>D</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>5</u> TOWNSHIP <u>12S</u> RANGE <u>33E</u> N.M.P.M.	10. Field and Pool, or Wildcat Bagley Penn, North
15. Elevation (Show whether DE, RT, GR, etc.) 4286 DF	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Set cement retainer @ 7350'.
- Pumped 200 sx Class C cement below retainer and 25 sx on top of retainer. Calculated TOC @ 7100'. Shot off 5 1/2" csg. @ 5850' and pulled free.
- Spotted 150 sx Class C cement to 5906' over 5 1/2" casing.
- Loaded hole w/10# gelled brine. Spotted 150 sx Class C cement @ 5906' over 5 1/2" casing stub.
- Spotted 50 sx Class H cement over top of Glorieta formation. Pulled to 3700' and spotted 200 sx Class H cement.
- Tagged top of cement plug @ 3280'. Perf'd 8 5/8" casing @ 1300' w/4 JS. Set 8 5/8" cement retainer @ 1293'. Loaded csg.-tbgs. annulus and press'd to 1000 PSI. Pumped 125 sx Class H cement below retainer and spotted 10 sx on top of retainer. Cut 8 5/8" casing off below flange. Placed 5 sx cement on top of 8 5/8" csg. Installed plugged and abandoned marker. Cleaned up location. P & A job complete.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED G. W. Tullos

TITLE G. W. Tullos  
Senior Production Engineer

DATE 2-9-78

APPROVED BY Eddie W. Seay

TITLE OIL & GAS INSPECTOR

DATE MAR 23 1978

CONDITIONS OF APPROVAL, IF ANY: