Form	9-331
(May	1963)

16.

D STATES DEPARTMENT OF THE INTERIOR verse side)

SUBMIT IN TRIPLI

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

GEO	OGICAL	SURVEY

NM-0202771-A

SUNDRY NOTICES AND REPORTS ON WELLS	O. IF INDIAN, ADDOTTED OR TRIBE NA
Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)	
	7 UNIT ACREMENT NAME

SUNDRY NOILES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	
I. OIL GAS OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
R. L. Burns Corporation	Vada Pruitt
3. ADDRESS OF OPERATOR	9. WELL NO.
c/o Oil Reports & Gas Services, Inc., Box 763, Hobbs, EM 88240	2
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT
1980' FSL & 660' FEL of Section 1	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
	Sec 1, 198, R34E

15. ELEVATIONS (Show whether DF, RT, GR, etc.) 13. STATE 14. PERMIT NO.

4321 OR Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOT	ICE O	F INTENTION TO:	SUBSEQUEN	T REPORT OF:	
TEST WATER SHUT-OFF		PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT		MULTIPLE COMPLETE	 FRACTURE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE		ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*	
REPAIR WELL	1	CHANGE PLANS		k & sidetrack	I
(Other)			(Note: Report results of Completion or Recompleti	multiple completion on Well on Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spotted 250 sacks Class "C" cement 25 calcium chloride, 15% sand on top of fish at 1344, 7:00 AM 7/11/75. Top of cement at 1250. Ran drill pipe & bit to dress cement; while dressing cement plug, drilled off plug at 1275. Drilled around junk to 3975. Totoos as follows: $1350 - 1 \frac{1}{2}$, $1625 - 2 \frac{3}{4}$, 1816 - 3, $2121 - 2 \frac{3}{4}$, $2665 - 1 \frac{1}{2}$, $3530 - \frac{1}{4}$, $3920 - \frac{3}{4}$.

Cemented 8 5/8" 32# & 24# J-55 casing at 3975 with 375 sacks Class "C" 2% calcium chloride. Plug down 2:30 PM 7/21/75. WOC 24 hours. Pressure tested casing with 1500# for 1 hour, held 0.K.

18. I hereby certify that the foregoing is true and correct Agent 7/31/75 TITLE DATE (This space for Federal or State office use) APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

HOBBS, NEW MEXICO