

OF COPIES RECEIVED

DISTRIBUTION

SANITAFE

FILE

U.S.G.S.

LAND OFFICE

OPERATOR

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease

State ☐

Fee ☒

5. State Oil & Gas Lease No.

1-E1 9S 33E

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER-

2. Name of Operator

Ike Lovelady, Inc.

3. Address of Operator

P.O. Drawer 2666; Midland, Texas 79702

4. Location of Well

UNIT LETTER E, 1980 FEET FROM THE north LINE AND 660 FEET FROM

THE west LINE, SECTION 1 TOWNSHIP 9-S RANGE 33-E N.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name

Sheridan

9. Well No.

1

10. Field and Pool, or Wildcat

Vada-Penn

15. Elevation (Show whether DF, RT, GR, etc.)

GL 4334

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOBS ☐

OTHER ☐

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-7-79 Hole was filled prior to moving in Csg. Pulling rig W/10# mud, 68 Vis., 5.2 water loss. Set 5-1/2" Baker CIBP @ 8000' W/35' cement on top. Shot 5-1/2" csg. @ 6950' could not pull, shot Csg. @ 6021' pull & lay down 5-1/2" Csg. RIH with Tbg. to 6016' could not get into stub of 5-1/2" Csg. Set 50 Sks cement plug Class 'C' 2% Calcium Chloride @ 6016'. Pull out. Cement waited 4 hrs. Tag plug @ 5827'. Pull Tbg. up to 5278' & set 25 Sks plug. Pull Tbg. up to 3926'. Set 30 Sk Plug. Pull out cement. Shut down over night. RIH with Tbg. Tag cement plug @ 3773'. POH W/Tbg. Weld onto 8-5/8" Csg. Worked 8-5/8" Csg. Shot @ 1042'. Pull & lay down 8-5/8" Csg. RIH W/ Tbg. Set 45 Sks. cement plug @ 1070'. Pull Tbg. up hole, waited 3 hrs. Tag plug @ 969'. POH W/Tbg. 450' set 70 Sk. plug @ 450'. Pull up hole with Tbg., waited 2 hrs. Tag plug @ 370'. POH with Tbg. Put 5 Sk. cement @ surface & install dry hole marker.

NOTE: (Will call New Mexico Oil Conservation Commission when Location ready to inspect.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Paul J. Sims Paul J. Sims

TITLE Mgr. of Drlg. & Production

DATE September 24, 1979

APPROVED BY

David Catalan

TITLE

OIL & GAS INSPECTOR

DATE

DEC 14 1983

CONDITIONS OF APPROVAL, IF ANY: