

OF COPIES RECEIVED	
DISTRIBUTION	
SAFETY	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator I. W. Lovelady	8. Farm or Lease Name Sheridan
3. Address of Operator P. O. Drawer 2666; Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>E</u> , <u>1980'</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>1</u> TOWNSHIP <u>9S</u> RANGE <u></u> NMPM.	10. Field and Pool, or Wildcat Vada Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4334.2 GR	12. County Lee

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER <input type="checkbox"/>
REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	
ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

9/8/75 Drilled 11" hole to 3876'. RIH W/Halliburton guide shoe, 1 Jt. new 32# J-55 8Rd thd. Csg. 43.50', insert float, 30 Jts. new 32# J-55 8Rd Csg. 1381', 53 Jts. new 24# J-55 8Rd Csg. 2360', and 3 Jts. new 32# J-55 on top 90'. Cemented @ 3876' W/275 Sks. Class "C" cement W/2% CaCl. P. D. @ 12:00 A.M. 9/9/75. W.O.C. 18 Hrs. Nipped up and tested csg. and cement job to 1000 PSI for 30 minutes. Test OK. Prep. to drill 7-7/8" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNED <u>R. L. Hamman Jr.</u>	TITLE <u>Production Supt.</u>
DATE <u>9/10/75</u>	
APPROVED BY <u>John Runyan</u> Geologist	TITLE <u>Geologist</u>
DATE <u>SEP 15 1975</u>	
CONDITIONS OF APPROVAL, IF ANY:	