

	O. D.	I. D.	LENGTH	DEPTH
Drill Pipe or Tubing				
Reversing Sub				
Water Cushion Valve				
Drill Pipe	4 1/2" XH	3.826"	10989'	
Drill Collars	4 1/2" XH	2.25"	746'	
Handling Sub & Choke Assembly				
Dual CIP Valve				
Dual CIP Sampler				
Hydro-Spring Tester	5"	.75"	60.21"	11767'
Multiple CIP Sampler	5"	.87"	54.19"	
			54.94"	
Extension Joint (2)	5"	.87"	54.94"	
AP Running Case	5"	3.06"	49.63"	11788'
Hydraulic Jar	5"	1.75"	60"	
VR Safety Joint	5"	1"	33.40"	
Pressure Equalizing Crossover	5"	1/2"	12"	
Packer Assembly	6 3/4"	1.75"	72.33"	11799'
Distributor				
Packer Assembly	6 3/4"	1.75"	72.33"	11805'
Flush Joint Anchor	5 3/4"	3.50"	30'	
Pressure Equalizing Tube	1"	1/2"	36'	
Blanked-Off B.T. Running Case	5"	2.44"	48.71"	11841'
Drill Collars				
Anchor Pipe Safety Joint				
Packer Assembly	6 3/4"	1.75"	72.33"	11848'
Distributor				
Packer Assembly	6 3/4"	1.75"	72.33"	11854'
Anchor Pipe Safety Joint				
Side Wall Anchor	6 3/4"	1.62"	62.57"	11860'
Drill Collars				
Flush Joint Anchor				
Blanked-Off B.T. Running Case				
Total Depth				11900'