

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
E 9713

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input checked="" type="checkbox"/> GAS <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
Pennzoil Company	State "11"
3. Address of Operator	9. Well No.
P. O. Drawer 1828 - Midland, Texas 79701	1
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER L, 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 11 TOWNSHIP 10-S RANGE 32-E NMPM.	North Mescalero <i>Penn</i>
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
4290.8 GR.	Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-05-75 Spudded well @ 3:30 P.M. - Drilled 17 1/2" hole to 400'. Ran 13 3/8", H-40 48#, ST&C casing & cemented @ 400' w/420 sx. Class "C" cement. Cement circulated. Plug down @ 2:00 A.M. 12-06-75.

Drilled 11" hole to 3420'. Ran 8 5/8", 24 & 32#, K-55, ST&C casing & cemented w/320 sx. Class "C" cement. Plug down @ 10:30 P.M. 12-09-75. WOC 24 hours. Tested casing w/1500# for 30 minutes. Held O.K. - Top of cement 2220' by Temperature survey.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <i>Donald M. ...</i>	TITLE Drilling Superintendent	DATE 12-31-75
APPROVED BY <i>[Signature]</i>	TITLE <i>[Signature]</i>	DATE <i>[Signature]</i>
CONDITIONS OF APPROVAL, IF ANY:		

U.S. DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
JAN 6 1977
OIL CONSERVATION COMMISSION
DENVER, CO