

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R142

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
H. L. BROWN, JR.

3. ADDRESS OF OPERATOR
P. O. Box 2237, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1980 FNL, 1980 FWL

14. PERMIT NO.
4047.1 GL

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
4047.1 GL

5. LEASE DESIGNATION AND SERIAL NO.
LC 069300

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Mobil Atlantic Federal

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Wildcat

11. SEC. T, R. 1/4, OR BEE. AND SURVEY OR AREA
Sec. E, T-9S, R-37E

12. COUNTY OR PARISH
Lea

13. STATE
New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Completion and P&A

REPAIRING WELL

ALTERING CASING

ABANDONMENT

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

2-11: Prep to run DST #3 - packer failed.
2-12: Ran DST #4 (12,280-12,412') (Devonian)
Recovered 3000' water blanket + 465' mud + 5369' formation water, no show oil or gas. Pressure indicated plugging.
IH 6428, IF 3703, FF 4412 - 1½ hrs., No ISI or FSI, FH 6212, BHT 200°
Now going in hole open ended, prep to plug.
2-13: TD 12,412'. Wen in hole open ended, set plugs at:
12,000' 75sks
10,869' 50 sks
8,778' 50 sks
7,680' 50 sks
5,504' 50 sks
4,225' 50 sks

Laid down drill pipe and collars, nipped down. Rig released 7AM, 2-13-76.

18. I hereby certify that the foregoing is true and correct

SIGNED Jack R. McGraw

TITLE Drig. & Prod. Manager

(This space for Federal or State office use)

DATE Feb. 13, 1976

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE