

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	1600	T. Canyon	9192	T. Ojo Alamo	T. Penn. "B"
T. Salt	1700	T. Strawn		T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	2190	T. Atoka	10,120	T. Pictured Cliffs	T. Penn. "D"
T. Yates	2088	T. Miss	10,400	T. Cliff House	T. Leadville
B. Yates	2377	T. Devonian	10,068	T. Menefee	T. Madison
T. Rivers	2930	T. Silurian		T. Point Lookout	T. Elbert
T. Queen		T. Montoya		T. Mancos	T. McCracken
T. Grayburg		T. Simpson		T. Gallup	T. Ignacio Qtzte
T. San Andres	3472	T. McKee		Base Greenhorn	T. Granite
T. Glorieta	4868	T. Ellenburger		T. Dakota	T.
T. Paddock	5180	T. Gr. Wash		T. Morrison	T.
T. Blinberry	Clfk. 5632	T. Granite		T. Todilto	T.
T. Tubb	6328	T. Delaware Sand		T. Entrada	T.
T. Drinkard		T. Bone Springs		T. Wingate	T.
T. Abo	7187	T.		T. Chinle	T.
T. Wolfcamp	3824	T.		T. Permian	T.
T. Penn.		T.		T. Penn. "A"	T.
T. Cisco (Bough C)	8887	T.			

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	6	6	Cellar				
6	1623	1617	Red bed				
1623	1687	64	Anhydrite				
1687	2180	493	Anhy., Salt & Shale				
2180	2260	80	Anhy				
2260	2377	117	Sand & Shale				
2377	3472	1095	Sand Shale, Salt, Anhy.				
3472	4860	1388	Anhy, Dol., Lime				
4860	5170	310	Dol., Anhy & Sand				
5170	5220	50	Dol.				
5220	5632	412	Dol., Sand, Shale, Anhy.				
5632	6330	698	Dol, Sand, Shale, Anhy. w/salt stringers				
6330	6500	170	Sand and Shale				
6500	7177	677	Dol. and Anhy.				
7177	7700	523	Shale w/Dol. stringers				
7700	8204	504	Dol. and Anhy.				
8204	8350	146	Dol., Chert & Shale				
8350	10000	1650	Lime and Shale				
10000	10430	430	Lime, Shale & Sd.				
10430	10528	98	Lime				
10528	10577	49	Chert				
10577	10820	243	Lime				
10820	11068	248	Shaley Lime				
11068	11087	TD 19					