

COPIES RECEIVED		
DISTRIBUTION		
NTA FE		
ILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-63

<p align="center">SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</p>		<p>5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/></p>
<p>1. Name of Operator <u>Natomas North America, Inc.</u></p>		<p>5. State Oil & Gas Lease No.</p>
<p>2. Address of Operator <u>5251 Westheimer, Suite 700, Houston, TX 77056</u></p>		<p>7. Unit Agreement Name</p>
<p>3. Location of Well UNIT LETTER <u>M</u> <u>860</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>19</u> TOWNSHIP <u>10-S</u> RANGE <u>32-E</u> NMPM.</p>		<p>8. Farm or Lease Name <u>New Mexico State</u></p>
<p>15. Elevation (Show whether DF, RT, GR, etc.) <u>4381 Gr.</u></p>		<p>9. Well No. <u>1</u></p>
<p>16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data</p>		<p>10. Field and Pool, or Wildcat <u>Wildcat</u></p>
<p>NOTICE OF INTENTION TO:</p> <p>PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/></p> <p>TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/></p> <p>PULL OR ALTER CASING <input type="checkbox"/> OTHER <u>Set & cmt. 8 5/8" intermediate casing</u> <input checked="" type="checkbox"/></p>		<p>12. County <u>Lea</u></p>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to 3550' and ran 8 5/8" casing to 3550'. Halliburton cemented W/1070 sx Howco - lite containing 10# salt/sack, 5# Gilsomite/sack, and 1/4# floccel/sack and W/300 sx Class "C" cement containing 2% CaCl₂. Had full returns but did not circulate cement. Ran Schlumberger temperature survey to locate top of cement. Received verbal permission from Mr. Les Clements to drill ahead on 3-11-78. Tested BOPE and casing prior to drilling out. Schlumberger is sending copy of temperature survey to the Conservation Commission.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

<p>SIGNED <u>Richard A. Porter</u></p> <p>Original Signed by Jerry Sexton Dist 1, Supt.</p>	<p>TITLE <u>Division Production Manager</u></p>	<p>DATE <u>3-16-78</u></p> <p>MAR 21 1978</p>
<p>APPROVED BY _____</p>	<p>TITLE _____</p>	<p>DATE _____</p>
<p>CONDITIONS OF APPROVAL, IF ANY:</p>		