| | ·. | |
|--|---|--|
| NO. OF COPIES RECEIVED | | _ |
| DISTRIBUTION | | Form C-103 Supersedes Old |
| SANTAFE | NEW MEXICO OIL COMPERMATION COMMISSION | C-102 and C-103 |
| FILE | NEW MEXICO OIL CONSERVATION COMMISSION | Effective 1-1-65 |
| U.S.G.S. | | |
| LAND OFFICE | | 5a. Indicate Type of Lease |
| OPERATOR | | State X Fee |
| | | 5. State Oil & Gas Lease No. L-2775 |
| SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. (DO NOT USE THIS FORM FOR PROPOSALS.) | | mminimini |
| (DO NOT USE THIS FORM FOR PROP USE "APPLICATION | OSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. DN FOR PERMIT _** (FORM C-101) FOR SUCH PROPOSALS) | |
| 1. | | 7. Unit Agreement Name |
| WELL WELL X | OTHER- | |
| 2. Name of Operator | | 8. Farm or Lease Name |
| Morris R. Antwei | .1 | Landlady |
| 3. Address of Operator | | 9. Well No. |
| Box 2010, Hobbs, | New Mexico 88240 | 1 |
| 4. Location of Well | | 10. Field and Pool, or Wildcat |
| UNIT LETTER B . 6 | 60 FEET FROM THE North LINE AND 1980 FEET FR | Wildcat |
| East S 12-S 32-E NMPM | | |
| | | ~ (|
| | 15. Elevation (Show whether DF, RT, GR, etc.) | |
| | | 12. County |
| | 4403' GR | Lea ///////// |
| Check A _I | ppropriate Box To Indicate Nature of Notice, Report or C | ther Data |
| NOTICE OF INT | | NT REPORT OF: |
| | | |
| PERFORM REMEDIAL WORK | PLUG AND ABANDON REMEDIAL WORK | ALTERING CASING |
| TEMPORARILY ABANDON | COMMENCE DRILLING OPNS. | PLUG AND ABANDONMENT |
| PULL OR ALTER CASING | CHANGE PLANS CASING TEST AND CEMENT JOB | |
| | OTHER | |
| OTHER | | _ |
| 17. Describe Proposed or Completed Oper work) SEE RULE 1103. | rations (Clearly state all persinent details, and give persinent dates, includir | ng estimated date of starting any proposed |
| D-111-1111 2-1- | / | |
| prilled it noie | to TD 3700'. Ran and cemented 102 jts | 6. 8-5/8" 24 & 32# |
| J-55 casing @ 370 | 0' with 1100 sx. Halliburton lite ceme | nt containing |
| 15#/sx salt, 3#/s: | x. gilsonite & $1/2\#/sx$. flocele follow | red by 300 sx |
| Class "C" cement | containing 2% CaCl ₂ . Plug down 3:50 A | M 20 August 1978 |
| Circulated out 79 | sx. cement. WOC 18 hrs. Tested casi | ng with 2000 psi- |
| 30 mins_OK Dril | led out and drilling ahead with 7-7/8" | ng with 2000 psi- |
| 30 mins-on. Diff. | red out and diffiling ahead with 7-1/8 | DIT. |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

ORIGINAL SIGNED BY
NATHAN E. CLEGG
ONDITIONS OF APPROVAL, IF ANY:

Approved by Certify that the information above is true and complete to the best of my knowledge and belief.

Agent
ORIGINAL SIGNED BY
NATHAN E. CLEGG
TITLE
ONTE

Approved by OIL & GAS INSP.

KELEINE

AUG22 1978

City Constitution in Manager in M.