

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANITARY	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

<p><b>SUNDRY NOTICES AND REPORTS ON WELLS</b> DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - M" (FORM C-101) FOR SUCH PROPOSALS.)</p>		<p>6a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/></p> <p>5. State Oil &amp; Gas Lease No. <b>L-1911</b></p>
<p>1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-</p> <p>2. Name of Operator <b>Signor Corporation</b></p> <p>3. Address of Operator <b>900 N.E. Loop 410, San Antonio, Texas 78209</b></p> <p>4. Location of Well UNIT LETTER <b>0</b> FEET FROM THE <b>South</b> LINE AND <b>1980</b> FEET FROM THE <b>East</b> LINE, SECTION <b>21</b> TOWNSHIP <b>11 S</b> RANGE <b>38 E</b> N.M.P.M.</p>	<p>7. Unit Agreement Name</p> <p>8. Farm or Lease Name <b>Zink State</b></p> <p>9. Well No. <b>1</b></p> <p>10. Field and Pool, or Wildcat <b>Wildcat</b></p>	
<p>15. Elevation (Show whether DF, RT, GR, etc.) <b>3896.6 GR -- 3910.1 RT</b></p>	<p>12. County <b>Lea</b></p>	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 16" hole to 450' with spudder--reamed to 18". Set 11 joints 13-3/8", 54.50# new casing at 440' below ground level. Cemented with 500 sacks of Class "C" cement plus 1/4# Flocele per sack. Plug down at 12:15 PM 1/12/79. Circulated cement to surface. Moved out spudder. Moved in MGF Drilling Company Rig #1. Nippled up BOPs and tested casing and BOPs-1000# held for 30minutes. Tested 1/19/79.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED James W. Currutt TITLE Production Manager DATE 1/20/79

APPROVED BY Jerry Sexton TITLE Dir. L. Supv. DATE JAN 23 1979

CONDITIONS OF APPROVAL, IF ANY: