

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>	
5. State Oil & Gas Lease No. B-10356	
SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)</small>	
1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator John S. Goodrich	8. Name of Lease Name Amerada State
3. Address of Operator 300 W. Texas, Suite 718 Midland, Texas 79701	9. Well No. 2
4. Location of Well UNIT LETTER G 1830 FEET FROM THE North LINE AND 1980 FEET FROM East THE 33 LINE, SECTION 11-S TOWNSHIP 33-E RANGE 33-E NORTH.	10. Field and Pool, or Wellbore Bagley, Penn, North
11. Elevation (Show whether DE, RE, GR, etc.) 4267 GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 103.

A bridge plug with 35' of cement on top is to be set at 9400'. The 5½" casing will be parted at the top of cement behind the 5½" casing at 4800' and recovered. A 100' cement plug will be placed 1/2 in and 1/2 out of the 5½" casing stub. Then 100' cement plugs to be set at 3800' (8 5/8" @ 3750') and above the top of Salt at 1770' plus a 10 sx cement plug at the surface.

Mud laden brine to be used between plugs and a marker installed by Carr Well Service who will plug this well.

100' PLUG @ TOP of B LORIST

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *J. Goodrich* TITLE Operator DATE 11-27-92

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE DEC 01 '92

CONDITIONS OF APPROVAL, IF ANY: