

## 'L CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.B.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L-3766	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Morris R. Antweil		Lucky Larry
3. Address of Operator		9. Well No.
Box 2010, Hobbs, New Mexico 88240		1
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>0</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM		No. Caprock-Miss.
THE <u>East</u> LINE, SECTION <u>5</u> TOWNSHIP <u>12-S</u> RANGE <u>32-E</u> NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
4404' GR		Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 12-1/4" hole to 3700'. Ran 90 jts. 8-5/8" 24# & 32# J-55 casing and cemented @ 3700' with 1300 sx Halliburton Lite cement containing 15#/sx. salt, 3#/sx gilsonite and 1/2#/sx Flocele and 300 sx Class "C" cement containing 2% CaCl<sub>2</sub>. Plug down @ 3:30 PM 6 April, 1980. Circulated 110 sx. WOC 18 hrs. Tstd casing w/1500 psi-30 mins.- OK. Drilled out and drilling ahead w/7-7/8" bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R M Williams TITLE Agent DATE 16 May, 1980

APPROVED BY Jerry Sexton TITLE Dist. 1. Supv. DATE May 22 1980

CONDITIONS OF APPROVAL