

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ Dry Hole
2. NAME OF OPERATOR  
Pioneer Production Corporation
3. ADDRESS OF OPERATOR  
P. O. Box 2542 Amarillo, Texas 79189
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FWL & 1980' FSL  
AT TOP PROD. INTERVAL: 660' FWL & 1980' FSL  
AT TOTAL DEPTH: 660' FWL & 1980' FSL
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☒
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON\* ☒
- (other) \_\_\_\_\_

## SUBSEQUENT REPORT OF:

RECEIVED

SEP 16 1980

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

## 5. LEASE

NM-34448

## 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A

## 7. UNIT AGREEMENT NAME

N/A

## 8. FARM OR LEASE NAME

Federal 18

## 9. WELL NO.

1

## 10. FIELD OR WILDCAT NAME

Undesignated Bough San Andres

## 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 18, T9S-R36E

## 12. COUNTY OR PARISH

Lea

## 13. STATE

NM

## 14. API NO.

## 15. ELEVATIONS (SHOW DF, KDB, AND WD)

4096 GL, 4111 DF, 4112 KB

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- (1) Spot 12.1 cu. ft. cement class "C" plug from PBTD 4870' to 4735', 50' above top perf.
- (2) Pull free point on 4 1/2" casing and cut off casing by shooting off collar. Anticipate pulling 1000' of 4 1/2" casing.
- (3) Spot 33 cu. ft. cement class "C" plug from 50' above to 50' below cut off casing.
- (4) Spot 40 cu. ft. cement class "C" plug from 50' above to 50' below 8 5/8" surface casing shoe.
- (5) Spot 10 sack cement class "C" plug at surface. Set 4" X 4' surface marker well info.

NOTE: 9.5#/gal mud to be spotted between cement plugs as needed.

Subsurface Safety Valve: Manu. and Type

N/a

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Richard H. StewartTITLE Prod. Engineer DATE August 22, 1980(Orig. Sgd.) GEORGE H. STEWART

(This space for Federal or State office use)

ACTING DISTRICT ENGINEER

SEP 18 1980

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: