

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well
2. NAME OF OPERATOR
Pioneer Production Corporation
3. ADDRESS OF OPERATOR
P. O. Box 2542, Amarillo, TX 79189
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 660' FWL of Sec. 18
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☒
☐
☐
☐
☐
☐

RECEIVED

JUL 2

(No report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

5. LEASE
NM 34448
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Federal 18
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Undesig. Bough San Andres Gas
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 18, T9S, R36E
12. COUNTY OR PARISH
Lea
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
4096 GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 6-18-80 - Perforated San Andres with 1 jet each: 4829-31-32-35-36-39-41-43-47-53-54-55-61-63 with 3 1/8" csg. guns. Acidized with 1500 gals. 15% DS-30, swabbed back load and further stimulated with 8000 gals. Series 72 Type 20 Acid. Swab tested 12 BOPD and 108 BWPD.
- 6-25-80 - Perforated San Andres with 1 jet each: 4785-86-87-92-93-95-96-4802-03-05 with 3 1/8" csg. guns. Acidized with 1500 gals. 15% DS-30. Swabbed approx. 1 BO and 96 BW.
- 6-28, 29-80 Attempted to open cementer @ 2228' unable to pump into @ 2500#.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John R. Endrey TITLE Petroleum Engineer DATE 7-1-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

JUL 14 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO