

UNITED STATES N. M. DEPT. OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
HOBBS, NEW MEXICO 88240

Form approved.
Budget Bureau No. 1004-01-5
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.
NM 23020

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug into a different reservoir.
Use "APPLICATION FOR PERMIT" for such.

RECEIVED
FEB 2 12 02 PM '89

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. NAME OF OPERATOR
Rhonda Operating Company

3. ADDRESS OF OPERATOR
500 N. Loraine, Suite 1000, Midland, TX 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
1980' from the South line and 660' from the West line of
Section 33.

14. PERMIT NO.
15. ELEVATIONS (Show whether DP, RT, GR, etc.)
3928.4 KB

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal 33

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Sawyer San Andres
(Associated)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 33, T9S-R38E, NMPM

12. COUNTY OR PARISH
Lea

13. STATE
NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETION ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐
REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☒

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

WELL SPECS: 8-5/8" casing @ 413'; cement circulated to surface.
5-1/2" casing @ 5099'; cement circulated to surface.
Perforations 4952'-5001'.

WORK PERFORMED:

1/26/89 MIRU Pool Well Service. Pulled rods, pump.
1/27/89 Set cast iron bridge plug on tubing at 4843'. Circulated hole with 9.5# mud laden fluid. Spotted 5 sack cement plug 4843' to 4795'. Spotted down tubing 25 sack cement plug 2457' to 2210'. Spotted down tubing 25 sack cement plug 472' to 199'. Cut off wellhead 3' below ground level. Spotted 10 sack cement plug at surface. Installed dry hole marker. Rigged down Pool.

Cleared location of junk and equipment. covered pit. Cleaned location.

Well P&A 1/27/89. FINAL REPORT.

18. I hereby certify that the foregoing is true and correct

SIGNED Richard Lemon TITLE Agent

DATE 2/26/89

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____

DATE 3-15-89

CONDITIONS OF APPROVAL, IF ANY:

Approved as to _____
Liability under bond of _____ and
surface restoration is completed.

*See Instructions on Reverse Side