

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Rhonda Operating Co.

3. ADDRESS OF OPERATOR

511 N. Main, Midland, TX 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660 FWL & 1980 FSL

AT TOP PROD. INTERVAL: 660' FWL & 1980' FSL

AT TOTAL DEPTH: 660' FWL & 1980' FSL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Well Casing ☒

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED
JUN 27 1980
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

5. LEASE

N. M. 23020

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 33

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Sawyer (San Andres)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 33, T-9-S, R-33-E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
KB 328.4 DF 3927.4 GL 3917.4

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

April 10, 1980: Drilling at 413' in red bed. Deviation at 413' = 3/4°.

Set 10 joints 8 5/8" casing with 12' landing joint at 403'.

Cemented with 250 sacks class "C" cement with 2% CaCl₂ circulated cement to surface.

April 22, 1980: T.D. at 5099'. Cemented 121 joints 5 1/2"

14# Grade J ST&C casing with combination float shoe and latch down plug with 350 sacks class "C" cement with 50/50 pozmix, 2% gel, 6# salt and .3% CFR₂. Estimated top of cement 4050. Set D.V. Tool at 2399.5' and cemented with 500 sack halliburton lite with 25# per sack flocel. Circulated 20 barrels cement to surface, from D.V. tool.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ralph H. May

TITLE Agent

DATE June 26, 1980

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUL 1 1980

Set
**U. S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO**