

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Rhonda Operating Co.
3. ADDRESS OF OPERATOR
511 N. Main, Midland, TX 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660 FWL & 1980 FSL
AT TOP PROD. INTERVAL: 660' FWL & 1980' FSL
AT TOTAL DEPTH: 660' FWL & 1980' FSL
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Well Casing ☒

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED
JUN 27 1980
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

5. LEASE
N. M. 23020
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Federal 33
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Sawyer (San Andres)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 33, T-9-S, R-33-E
12. COUNTY OR PARISH 13. STATE
Lea New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3928.4 DF 3927.4 GL 3917.4

(Note: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

April 10, 1980: Drilling at 413' in red bed. Deviation at 413' = $3/4^{\circ}$.

Set 10 joints 8 5/8" casing with 12' landing joint at 403'.

Cemented with 250 sacks class "C" cement with 2% CaCl_2 circulated cement to surface.

April 22, 1980: T.D. at 5099'. Cemented 121 joints 5 1/2"

14# Grade J ST&C casing with combination float shoe and latch down plug with 350 sacks class "C" cement with 50/50 pozmix, 2% gel, 6# salt and .3% CFR_2 . Estimated top of cement 4050. Set D.V. Tool at 2399.5' and cemented with 500 sack halliburton lite with 25# per sack floccel. Circulated 20 barrels cement to surface, from D.V. tool.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ralph H. Vurey TITLE Agent DATE June 26, 1980

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JUL 1 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO