

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Dome Oils, Inc.
3. ADDRESS OF OPERATOR One Marienfeld Place, Suite 290, Midland, Texas 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL, 1980' FEL
AT TOP PROD. INTERVAL: 660' FSL, 1980' FEL
AT TOTAL DEPTH: 660' FSL, 1980' FEL
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(other) Spud well & set 8 5/8" surface casing

5. LEASE
LC063623-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Dome-Wickson et al Fed. 5
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Wildcat
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 5, T-10-S, R-38-E
12. COUNTY OR PARISH
Lea
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3920.3 GR

RECEIVED
NOTE: Report results of multiple completion or zone change on Form 9-330.
JUL 22 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-2-80 Spud well @ 9:30 P.M.

7-3-80 Drilled to 426'. POH to run casing.

7-4-80 TD 426'. Ran 12 jts. 8 5/8" 24#, K-55, ST&C casing and set @ 426'. Cemented with 250 sks Class "C" plus 2% CaCl₂. Circulated out 54 sks. PD @ 12:00 Noon 7-3-80. WOC 8 hrs. Cut off casing. NU BOP. Pressure tested casing to 1000 psi - held OK.

7-5-80 Drilling @ 1056'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED AS Raut TITLE Agent DATE 7-18-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

JUL 23 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO