

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐ P&A  
2. NAME OF OPERATOR  
Yates Petroleum Corporation  
3. ADDRESS OF OPERATOR  
207 South 4th St., Artesia, NM 88210  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 330 FSL & 660 FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:  
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  
TEST WATER SHUT-OFF ☐ ☐  
FRACTURE TREAT ☐ ☐  
SHOOT OR ACIDIZE ☐ ☐  
REPAIR WELL ☐ ☐  
PULL OR ALTER CASING ☐ ☐  
MULTIPLE COMPLETE ☐ ☐  
CHANGE ZONES ☐ ☐  
ABANDON\* ☐ ☒  
(other) ☐ ☐

5. LEASE NM 28036  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Hilliard USA  
9. WELL NO.  
1  
10. FIELD OR WILDCAT NAME  
Jenkins SA  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit P, Sec. 17-T9S-R35E  
12. COUNTY OR PARISH Lea 13. STATE NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4156' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.) 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plugged and abandoned well as follows:

Set CIBP at 4750'. Dumped 30' of cement on top of CIBP. Cut 4-1/2" casing at 4085'. Layed down 94 jts of 4-1/2" casing (4068') plus stub. Set 30 sacks Class "C" Neat cement plug from 4122-4055' across 4-1/2" sub. Set 10 sack plug at surface. Installed dry hole marker. Surface will be restored.

Verbal permission for plugging obtained from Mr. George Stewart, Minerals Management Service, Roswell, 8-25-82.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED George Stewart TITLE Engineering Secty DATE 8-30-82

(This space for Federal or State office use)

APPROVED BY George Stewart TITLE Engineering Secty  
CONDITIONS OF APPROVAL, IF ANY:

DATE 8-13-85