Form 9-331 Dec. 1973

REPAIR WELL

REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE

PULL OR ALTER CASING MULTIPLE COMPLETE

N. M. OIL CUNS. CUMMISSION P. O. BOX 100 **MEXICO 88240**

DEPARTMENT O GEOLOGIC.

Form Approved	i.	
Budget Bureau	No. 42-R1424	4

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE NM 28036 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME
1. oi gas other P&A	Hilliard USA 9. WELL NO.
2. NAME OF OPERATOR Yates Petroleum Corporation 3. ADDRESS OF OPERATOR	1 10. FIELD OR WILDCAT NAME Jenkins SA
207 South 4th St., Artesia, NM 88210 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 330 FSL & 660 FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit P, Sec. 17-T9S-R35E 12. COUNTY OR PARISH 13. STATE Lea NM 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	15. FLEVATIONS (SHOW DF, KDB, AND WD)

4156' GR

(NOTE: Report results of multiple completion or zone

MINERALS MGMT. SERVICE ROSWELL, NEW MEXICO

change on Form 9-330.)

CHANGE ZONES XX ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to plug and abandon well as follows:

Will set a CIBP at 4750', cut 4-1/2" casing at 4090' and pull.

SUBSEQUENT REPORT OF:

Set 30 sacks cement plug at 4140-4000'.

Set 10 sacks cement plug at 50-surface.

Will install dry hole marker, clean and level location.

Verbal permission obtained for plugging from Mr. George Stewart, Minerals Management Service, Roswell, 8-25-82 by Mr. Eddie Mahfood.

Subsurface Safety Valve: Manu. and Type	Set @
18. I hereby certify that the foregoing is true and correct SIGNED LA	8-25-82
APPROVED BY CONDITIONS OF APPROVAL, IF ANY GET SEP 2 1982	RECEIVED
208	AUG 2 6 1982
JAMES A. GILLHAM DISTRICT SUPERVISOR *See Instructions on Reverse Side	OIL & GAS