

COPY TO O. G. C.
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other instructions
reverse side)

E*
re-

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

USANM28036

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

none

8. FARM OR LEASE NAME

U.S.A.

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

12. COUNTY OR PARISH

Lea

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Hilliard Oil & Gas, Inc.

3. ADDRESS OF OPERATOR
1190 Midland National Bank Tower Midland, TX 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

330' FSL & 660' FEL, Sec 17, T9S, R35E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugging Procedure

1st Plug 12,670'-12,470', Class "H" w/ .3% HR-4 (60 sx)
2nd Plug 9000'- 8850', Class "H" w/ .3% HR-4 (50 sx)
3rd Plug 7800'- 7650', Class "H" neat (50 sx)
4th Plug 5835'- 5400', Class "H" neat (50 sx)

8-5/8" intermediate casing is set @ 4095' and cemented to the surface.

Note: At this time Yates Petroleum will become the operator and try a completion in the San Andres formation.

18. I hereby certify that the foregoing is true and correct

SIGNED *Robert Elatt*

TITLE Drilling Engineer

DATE 1/19/81

(This space for Federal or State office use)

APPROVED *(Signature)* PETER W. CHESTER
CONDITIONS OF APPROVAL, IF ANY:

TITLE ACTING DISTRICT ENGINEER

DATE JAN 26 1981

Designation of Operator needed, Hanson Oil Corp. to Yates Petroleum.

*See Instructions on Reverse Side