

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLI
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME None
2. NAME OF OPERATOR Hilliard Oil & Gas, Inc.	8. FARM OR LEASE NAME USA
3. ADDRESS OF OPERATOR 1190 Midland National Bank Tower, Midland, Texas 79701	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 330' FSL & 660' FEL, Sec. 17, T-9-S, R-35-E	10. FIELD AND POOL, OR WILDCAT Wildcat
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 17, T-9-S, R-35-E
15. ELEVATIONS (Show whether DF, BT, or other) 4165 GR	12. COUNTY OR PARISH Lea
	13. STATE New Mexico

RECEIVED
NOV 13 1980
U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>	WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>	FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>	SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	(Other) Intermediate Casing Procedure <input type="checkbox"/>	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drilled 11" hole to 4095'.
2. Ran 103 joints (4103.83') of 8-5/8", 32# & 24#, K-55, ST&C.
3. Casing set at 4095' and cemented by Halliburton with 1200 sx HLC, 15# salt per sx, 5# Gilsonite, 1/4# Flocele per sx, 250 sx Class "C" with 1/4# Flocele per sx. Circulated cement returns to surface. Cementing completed at 3:00 PM, 11-1-80.
4. Compressive strength of 2025 psig after 12 hour waiting period. Pressure tested casing with 1000 psi for 5 minutes; no pressure drop.

RECEIVED
NOV - 6 1980
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

Robert E. Patterson

18. I hereby certify that the foregoing is true and correct

SIGNED Robert E. Patterson TITLE Drilling Engineer DATE November 4, 1980

(This space for Federal or State use)

APPROVED BY PETER W. CHESTER TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:
NOV 5 1980
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO
See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE : 1963-O-685229

8-47-485

NOV 18 1960