

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPL  
(Other instructions  
verse side)

E-  
re-

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-068035

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Brazos Petroleum Company

3. ADDRESS OF OPERATOR

708 Petroleum Bldg. - Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)  
At surface

1980' FNL & 1980' FEL, Section 18, T-9-S, R-38-E

RECEIVED

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Holcomb '18' Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Sawyer (San Andres)

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 18, T-9-S, R-38-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3953 GR

FFB 12 1981

12. COUNTY OR PARISH

13. STATE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

U.S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2-10-81 Latched onto overshot on Pengo retrievable bridge plug and pulled tubing and bridge plug out the hole, went in the hole with tubing bottom-to-top as follows:

2 jts. 2-3/8" 4.7# J55 EUE tbgs. O.E. Mud anchor	58.83'
2-3/8" 4.7# J55 EUE perforated nipple	3.00'
2" x 1-25/32" seating nipple	1.10'
1 jt. 2-3/8" 4.7# J55 EUE tbgs.	31.02'
Pengo 4-1/2" x 2-3/8" tubing anchor	2.45'
157 jts. 2-3/8" 4.7# J55 EUE tbgs.	4,869.18'
160 jts.	4,965.58'

Seating nipple @ 4906' KB datum, removed B.O.P., nipples up wellhead, started swabbing well @ 2:15 PM 2-9-81, left well open to test tank overnight, set (2) 210 bbls. tanks and 3' x 15' heater treater.

U.S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED

*Yasmin Bracey*

TITLE

Production Clerk

DATE

2-10-81

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED  
FEB 11 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO